



1. SLAB THICKNESS RANGE 2" - 6"
2. QUAD-DECK PANEL THICKNESS: 7", 8", 9", 10", 11" 12", 12½"
3. INSULATION LIP THICKNESS 2"
4. BOTTOM LONGITUDINAL REINFORCEMENT EXTEND THROUGH WALL
5. QUAD-DECK PANEL - REFER TO 2.
6. INTERIOR FINISH FASTEN TO QUAD-DECK Z-STRIPS AND TO QUAD-LOCK TIE FLANGES
7. QUAD-LOCK PANEL
8. VERTICAL REINFORCEMENT AS SPECIFIED
9. HORIZONTAL REINFORCEMENT AS SPECIFIED
10. QUAD-LOCK TIE (6" BLUE SHOWN)
11. EXTERIOR FINISH AS SPECIFIED
12. SLOPE AS SPECIFIED
13. DOWELS AS SPECIFIED
14. CONCRETE SURFACE FINISH AS SPECIFIED
15. NEGATIVE REINFORCEMENT
16. SLAB REINFORCEMENT 6x6 WWM OR LONG. & TRANS. REBAR
17. CONCRETE TO BE CALLED BY THE ENGINEER OF RECORD



Quad-Lock Building Systems Ltd.
 7398 - 132nd Street
 Surrey, BC V3W 4M7
 Canada
 888.711.5625 - Toll Free
 604.590.3111
 604.590.8412 - fax
 www.quadlock.com

PITCHED ROOF CONCRETE OVERHANG DETAIL QUAD-DECK PARALLEL TO WALL

DATE:	2009-01-21	SCALE:	NOT TO SCALE
REVISION NO.:	R-02	PROJECT:	
REVISION DATE:	2009-07-10	CUSTOMER:	
DRAWN BY:	Z. PROSTRAN	APPROVED BY:	H.M.K. & D.J.B.
			DRAWING NO.:
			QD-207

IT IS THE RESPONSIBILITY OF THE USER TO COMPLY WITH ALL APPLICABLE REGULATIONS AND BUILDING CODE REQUIREMENTS CONCERNING THE USE OF THESE PRODUCTS.
 IT IS FURTHER THE RESPONSIBILITY OF THE USER TO RESEARCH AND UNDERSTAND SAFE METHODS OF USE AND HANDLING OF THESE PRODUCTS.