



1. BLOCKING AS SPECIFIED
2. PLYWOOD CAP AS SPECIFIED
3. QUAD-LOCK WIRE TOP TIE (6" SHOWN)
4. QUAD-LOCK REGULAR 2.25" PANEL
5. QUAD-LOCK TIE (6" BLUE SHOWN)
6. EXTEND VERTICAL REINFORCEMENT INTO PARAPET WALL
7. HORIZONTAL REINFORCEMENT AS SPECIFIED
8. 2-#4 BARS AT TOP OF WALL
9. DOWELS AS SPECIFIED
10. QUAD-LOCK TIE (8" YELLOW SHOWN)
11. REINFORCED CONCRETE CORE
12. EXTERIOR FINISH AS SPECIFIED
13. FASTEN INTERIOR WALL FINISH TO QUAD-LOCK PLASTIC TIE FLANGES
14. REMOVE QUAD-DECK LIP AS SHOWN

15. DRAIN
16. QUAD-DECK PANEL
17. QUAD-DECK BOTTOM LONGITUDINAL BEAM REINFORCEMENT
18. INTEGRATED GALVANIZED STEEL Z-STRIPS FOR CEILING FINISH ATTACHMENT
19. SLAB REINFORCEMENT 6" x 6" [152mm x 152mm] WELDED WIRE MESH OR LONGITUDINAL AND TRANSVERSE REBAR
20. INSULATION LIP THICKNESS 2"
21. QUAD-DECK PANEL THICKNESS: 7", 8", 9", 10", 11" 12", 12 1/2"
22. SLAB THICKNESS RANGE 2" - 6"
23. BASE SHEET MEMBRANE
24. CAP SHEET MEMBRANE
25. SOPRADRAIN 10-G OR EQUIVALENT
26. MICROFAB OR EQUIVALENT
27. SOPRAFLOOR GROWING MEDIUM (TYPE X OR L) OR EQUIVALENT
28. VEGETATION
29. CONCRETE, WOOD OR STEEL CURB
30. GRAVEL OR PAVER
31. QUAD-LOCK TRACK
32. PRIMER
33. FLASHING AS SPECIFIED
34. REMOVE PANEL KNOBS AND SECURE WITH QUAD-LOCK TRACK

QUAD-LOCK
Building Systems Ltd.

Quad-Lock Building Systems Ltd.
7398 - 132nd Street
Surrey, BC V3W 4M7
Canada

888.711.5625 - Toll Free
604.590.3111
604.590.8412 - fax
www.quadlock.com

IT IS THE RESPONSIBILITY OF THE USER TO COMPLY WITH ALL APPLICABLE REGULATIONS AND BUILDING CODE REQUIREMENTS CONCERNING THE USE OF THESE PRODUCTS.
IT IS FURTHER THE RESPONSIBILITY OF THE USER TO RESEARCH AND UNDERSTAND SAFE METHODS OF USE AND HANDLING OF THESE PRODUCTS.

GREEN ROOF DETAIL

DATE:	2009-01-21	SCALE:	NOT TO SCALE
REVISION NO:	R-02	PROJECT:	
REVISION DATE:	2009-07-10	CUSTOMER:	
DRAWN BY:	Z. PROSTRAN	APPROVED BY:	H.M.K. & D.J.B.
		DRAWING NO:	QD-204